


Mobile hinged support rail Duo 950.50.12190

- for easy and flexible retrofitting on existing, preassembled mounting plate: 950.50.014XA, must be ordered separately
- for mobile use
- with two gripping levels arranged above each other
- upper rail is merged with the top rail at an angle of 135°
- upper rail (diameter 33 mm) for holding on to and providing support
- bottom rail (diameter 25 mm) starts at a distance of 250 mm from the front edge of the upper rail and is used for holding on to and for turning in from the side
- 700 mm projection, bracket 181 mm high and 130 mm wide
- can be folded upwards and, folded downwards with braking mechanism
- made of high-quality polyamide in HEWI colours 98 (signal white) or 99 (pure white)
- with continuous, anti-corrosion steel core and bracket made of steel with cover made of high-quality polyamide
- tool-free and quick installation by means of short, simple hanging
- secured against unintentional removal
- unlocking for flexible use by spring actuation
- with toilet roll holder 950.50.01090, toilet roll holder with WC flushing mechanism and function button (radio-controlled) 950.50.06290, 950.50.06390 and floor supports 950.50.020XA, 950.50.025XA and 950.50.026XA for retrofitting
- CE marking according to Directive 93/42 / EEC
- fulfils the ÖNORM B1600/1601 and SIA 500 requirements
- weight capacity 100 kg



Dimensions in mm



Colours




Basic colour

Alternative colours



Basic colour



Top rail

Technical information subject to alteration, 16th August 2019

HEWI Heinrich Wilke GmbH
Postfach 1260
D-34442 Bad Arolsen

Telefon: +49 5691 82-366
Telefax: +49 5691 82-99366
international@hewi.com
www.hewi.com

HEWI (UK) Limited
Holm Oak Barn, Beluncle Halt
Stoke Road
Hoo Kent ME3 9NT

Phone +44 1634 258 200
Fax +44 1634 250 099
info@hewi.co.uk
www.hewi.com