

### Half fitting with security escutcheon 162PCH22.230

in H-technology with roses according to DIN 18255 and EN 1906 made of polyamide, high-polished surface, consisting of: Lever handle.162.21PCH in mitre cut, made of high-quality polyamide with corrosion resistant steel insert, solid colour, diameter 21.3 mm, with stepped shoulder guide and groove, easily installed by latching the lever handle into the base parts pre-mounted on the door.

The latching can be released using the dismantling tool. Rose 305.21PCH, rose substructure made of synthetic material-stainless steel composite, can be used for left and right-hand opening doors. Fixed rotating bearing of the lever handle with automatically latching all-round locking and 5 mm journal as maintenance-free plain bearing with elastic compensating area and second journal in the neck of the lever handle. Concealed, non-loosening screwed joint with M4 screw and sleeve combination as well as the pivot disappearing into the door leaf.

Rose cap, round, made of high-quality polyamide, solid colour, diameter 55 mm, 10.5 mm high, flat, 1.5 mm wall thickness. Security escutcheon 306.23ES, in polyamide-steel composite External rose 55 mm diameter, 10.5 mm high, hardened base, conical shape, as protection against forced twisting off

Internal rose, FS type, 55 mm diameter, 10.5 mm high, concealed screw fixing, for installation in pairs, supplied with screws M 5,

Holes for profiled cylinder (Euro cylinder and KABA), for cylinder projections: 7 - 12 mm

The security escutcheon conforms to the requirements of DIN 18273

Designed and tested for the projects segment, user category to EN 1906 - Class 4 fire door fitting with spindle 9 mm, according to DIN 18273

user category: Class 4

Durability: Class 7

Door weight: No classification specified

Fire resistance: Class D1

Safety: Class 1



Corrosion resistance: Class 4

Burglary protection: Class 1

Design-type: A

Article no.: HEWI 162PCH22.230

### Dimensions



### Colors

